



Certificate number: 2410797 (1)

Issued 22/10/2024

Expires N/A 1+

Kiwa Regulation 4(KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Aquacheck Engineering Ltd

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/products/tmv-testing/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

Royal Barn Road
Castleton
Rochdale
OL11 3DT



KUKreg4

Product Certificate

Appendix to Certificate number: 2410797

The following products belong to this certificate

Reg4 approval no:	2410797
Section:	0030
Application no:	S2401003
Product description:	Single check valve assembly consisting of a single check valve cartridge housed within a DZR brass body. Maximum working pressure 16 bar.
Models:	Aquacheck 750MFS.
Size:	¾ BSP (F) x ¾ BSP (M).
Marking:	Aquacheck, CR, flow arrow and 750MFS on body.
Materials:	Non-metallic materials assessed (BS6920) to point of discharge. Non-metallic materials suitable for continuous use with cold water only.
Additional notes:	All water contact & exposed components satisfy opacity requirements.

Reg4 approval no:	2108721
Section:	0034
Application no:	S210221
Product description:	Double check valve assembly with a DZR brass body incorporating a brass test port. Maximum working pressure 16 bar. For cold water use only.
Models:	Tapcheck 500D.
Size:	¾" BSP(M) x ¾" BSP(F).
Marking:	Aquacheck, 500D, BS6282-5, Flow arrow, CR, TAPCHECK stamped on body
Materials:	Non-metallic materials assessed (BS6920) to point of discharge. Non-metallic materials suitable for continuous use with cold water only.
Additional notes:	All water contact & exposed components satisfy opacity requirements.

Reg4 approval no:	1910705
Section:	0026
Application no:	S190646
Product description:	Range of in-line single check valve assemblies consisting of a spring loaded resilient trim check valve cartridge housed in a DZR brass or chrome plated DZR brass body. Maximum working pressure 16.0 bar.
Models:	Brass body Aquacheck 500 - ½" BSP (F). Aquacheck 750 - ¾" BSP (F). Aquacheck 1000 - 1" BSP (F). Aquacheck 1250 - 1¼" BSP (F). Aquacheck 1500 - 1½" BSP (F). Aquacheck 2000 - 2" BSP (F). Chrome plated body Aquacheck 15 - 15mm compression. Aquacheck 22 - 22mm compression. Aquacheck 28 - 28mm compression.
Size:	½ to 2 and 15mm to 28mm.
Marking:	Aquacheck, model, CR and direction of flow arrow on body.
Materials:	Non-metallic materials assessed (BS6920) to point of discharge. Maximum operating temperature 85°C.
Additional notes:	All water contact & exposed components satisfy opacity requirements.

Product Certificate

Appendix to Certificate number: 2410797

Reg4 approval no:	1910713
Section:	0034
Application no:	S190647
Product description:	Range of double check valve assemblies consisting of two spring loaded resilient trim in-line check valve cartridges housed in a DZR brass or chrome plated DZR brass body. Maximum working pressure 16.0 bar
Models:	Aquacheck 15D – 15mm Aquacheck 22D – 22mm Aquacheck 28D – 28mm Aquacheck 15D CP – 15mm Aquacheck 22D CP – 22mm Aquacheck 28D CP – 28mm Aquacheck 5000 – ½" BSP(F) Aquacheck 750D - ¾" BSP(F) Aquacheck 500D - ½" BSP (F). Aquacheck 750D - ¾" BSP (F). Aquacheck 1000D - 1" BSP (F). Aquacheck 1000DR - 1" BSP (F). Aquacheck 1250D - 1¼" BSP (F). Aquacheck 1500D - 1½" BSP (F). Aquacheck 2000D - 2" BSP (F).
Size:	½ to 2 and 15mm to 28mm.
Marking:	Aquacheck, flow arrow, CR mark.
Materials:	Non-metallic materials assessed (BS6920) to point of discharge. Maximum operating temperature 85°C.
Additional notes:	All water contact & exposed components satisfy opacity requirements.